

UNI-CAT

The intelligent UNI-CAT is a “smart” Winder that can be used as both a Rewinder and an Unwinder. The UNI-CAT automatically synchronizes with the printer to match the speed and direction of the printer, which makes it the ideal companion for printers that back-feed or that are tension-sensitive. The UNI-CAT also senses when the end of roll is reached and automatically stops winding.



UNI-CAT-CHUCK

Technical Specifications	UNI-CAT
Max Roll Diameter (in)	12 (305mm)
Core Diameter (in) ¹	1 (25mm), 3 (76mm), 1- 4 (25mm - 101mm)
Max Media Width (in) ²	6 - 10 (152 - 254mm)
Max Roll Weight (lbs)	20 (9-kg)
Dimensions-HWD (in)	14 x 17 x 17 (356 x 432 x 432mm)
Weight (lbs)	29 - 31 (13 - 14kg)
Max Speed (ips) ³	50 (1,270mm)
Min Speed (ips)	0.5 (12.5mm)
Max Torque (in-oz)	90
Max RPM	186
Number of Flanges ⁴	1
Winding	Bi-directional, for internal and external winding
Control Panel	Maintenance-free soft-touch control panel with LED-Status-Indicators
Power Specifications	120 - 240VAC in, 15VDC 3A Out
Warranty	5 year limited warranty on Rewinder - 1 year limited warranty on Power Adaptor

1. Depends on which model you order: 1" (25mm), 3" CHUCK or Fin-Style (76mm), or 1" - 4" ACH (25mm - 101mm)

08.2021

2. Depends on which model width you order: 6" (152mm), 8" (203mm), or 10" (254mm)

3. Linear speed varies based on roll diameter and weight.

4. Two Guides are included: The Inner Guide Flange, as well as the Outer Media Guide Collar.