

Compact Bench Scales

SJ-HS

Series



SJ-1000HS SJ-2000HS SJ-5000HS SJ-5001HS SJ-12KHS SJ-20KHS SJ-30KHS



AND
A&D Australasia
"Excellence in Measurement"
www.andaustralasia.com.au

Features

- Large, removable stainless steel (SUS304) weighing pan, which is easy to wash and keep clean
- High-speed weighing in less than 1 second to increase your work efficiency
- Resolution up to 1/5000 (SJ-5001HS) for highly precise measurements
- Clearly visible LCD (with 25 mm character height) ensuring accurate reading of results
- Low-profile construction for storage in narrow shelves, which also helps when lifting heavy objects to the weighing pan
- Tare function to exclude the weight of the container from the weighing result
- Long battery life of approx. 2000 hours (optional AC adapter is also available)
 - Auto power off function so as not to waste battery power
 - Battery indicator that tells you the remaining battery level
- Four weighing units (g, lb, oz, and lb-oz) that can be switched with a single key
- Two side handles allowing easy carrying of the scale
- Zero tracking function to maintain the display at zero before measurement



The battery box makes it quick and easy to replace batteries.

Specifications

	SJ-1000HS	SJ-2000HS	SJ-5000HS	SJ-5001HS	SJ-12KHS	SJ-20KHS	SJ-30KHS	
Capacity x Resolution	g	1000 g x 0.5 g	2000 g x 1 g	5000 g x 2 g	5000 g x 1 g	12 kg x 5 g	20 kg x 10 g	30 kg x 20 g
	lb	2.2 lb x 0.001 lb	4.4 lb x 0.002 lb	11 lb x 0.005 lb	11 lb x 0.002 lb	26 lb x 0.01 lb	44 lb x 0.02 lb	66 lb x 0.05 lb
	oz	35 oz x 0.02 oz	70 oz x 0.05 oz	176 oz x 0.1 oz	176 oz x 0.05 oz	423 oz x 0.2 oz	705 oz x 0.5 oz	1058 oz x 1 oz
	lb-oz	2.2 lb x 0.1 oz	4.4 lb x 0.1 oz	11 lb x 0.1 oz	11 lb x 0.1 oz	26 lb x 1 oz	44 lb x 1 oz	66 lb x 1 oz
Repeatability (Std. deviation)	1 g	2 g	5 g	5 g	10 g	20 g	30 g	
Linearity	±1 g	±2 g	±5 g	±5 g	±10 g	±20 g	±30 g	
Sensitivity drift	±0.015% / °C (5 °C to 35 °C / 41 °F to 95 °F)							
Display	7 segment LCD (character height: 25 mm / 0.98 in.)							
Display update	10 times per second							
Operating conditions	-10 °C to 40 °C / 14 °F to 104 °F, 85%R.H. or less (no condensation)							
Power supply	Four D (R20P / LR20) batteries or AC adapter (optional)							
Battery life	Approximately 2,000 hours using alkaline batteries at 20 °C / 68 °F							
Weighing pan size	230 (W) x 190 (D) mm / 9.05 (W) x 7.48 (D) in.							
Dimensions	265 (W) x 250 (D) x 106 (H) mm / 10.4 (W) x 9.8 (D) x 4.2 (H) in.							
Net weight	2.2 kg / 4.85 lb					2.5 kg / 5.51 lb		
Calibration mass	1000 g	2000 g	5000 g	5000 g	10 kg	20 kg	30 kg	

Option AC adapter



AND
A&D Australasia
ACN 26 007 556 809
Head Office
32 Dew Street
THEBARTON South Australia 5031
Telephone (08) 8301 8100
Facsimile (08) 8352 7409

Victorian Office
39 Bakehouse Road
KENSINGTON Victoria 3031
Telephone (03) 9371 1555
Facsimile (03) 9372 1193

New South Wales Office
Unit 4, 14 Abbott Road
SEVEN HILLS New South Wales 2147
Telephone (02) 9674 5466
Facsimile (02) 9674 2544

sales@andweighing.com.au
www.andweighing.com.au

Your Dealer